



MOTOR FRAME	M	R		U1	U2	COUPLING SIZE	HA	HB	HD MAX.		HE	HF	HG MAX.	HH		HL	HP	HT MIN.	BASE PLATE PART NO.
		D=8.25	D=10						D=8.25	D=10				D=8.25	D=10				
182T/184T	4.50	3.75	5.50	1-1/8	7/8	6SC	18	64	12.25	14.00	7.5	61.5	4	0	0	4.5	1.25	3.5	3528-050
213T/215T	5.25	3.00	4.75	1-3/8	7/8	6SC	18	64	12.25	14.00	7.5	61.5	4	0	0	4.5	1.25	3.5	3528-050
254T/256T	6.25	2.00	3.75	1-5/8	7/8	7SC	18	64	12.25	14.00	7.5	61.5	4	0	0	4.5	1.25	3.5	3528-050
284T/286T	7.00	1.25	3.00	1-7/8	7/8	8SC	18	64	12.25	14.00	7.5	61.5	4	0	0	4.5	1.25	3.5	3528-050
324T/326T	8.00	0.25	2.00	1-5/8	7/8	8SC	18	64	12.25	14.00	7.5	61.5	4	0	0	4.5	1.25	3.5	3528-050
364T/365T	9.00	0	1.00	1-7/8	7/8	8SC	18	64	13.00	14.00	7.5	61.5	4	0.75	0	4.5	1.25	3.5	3528-050
IEC 100	3.94	4.31	6.06	[28]	7/8	6SC	18	64	12.25	14.00	7.5	61.5	4	0	0	4.5	1.25	3.5	3528-050
IEC 112	4.41	3.84	5.59	[28]	7/8	6SC	18	64	12.25	14.00	7.5	61.5	4	0	0	4.5	1.25	3.5	3528-050
IEC 132	5.20	3.05	4.80	[38]	7/8	7SC	18	64	12.25	14.00	7.5	61.5	4	0	0	4.5	1.25	3.5	3528-050

NOTES:

- 1) Motor back should not extend beyond base.
- 2) Mechanical coupling is "Woods Sure-Flex" type SC.