

Liquiflo Endura AB-Series Centrifugal Pumps

Selection & Availability

Model Code Position #	Code	Description	GROUP I: Pump Models			GROUP II:
			1.5 x 1 x 6	3 x 1.5 x 6	1.5 x 1 x 8	3 x 2 x 8
Position 1 Pump Type	B1	Air Barrier Pump	■	■	■	■
Position 2 Temperature Range	N	Normal (-60 to +350 °F)	■	■	■	■
Position 3 Pump Size	A	1.5 x 1 x 6	■	⊗	⊗	⊗
	B	3 x 1.5 x 6	⊗	■	⊗	⊗
	C	1.5 x 1 x 8	⊗	⊗	■	⊗
	1	3 x 2 x 8	⊗	⊗	⊗	■
Position 4 Basic Material of Construction	S	316 SS	■	■	■	■
	H	Alloy-C	CF	CF	CF	CF
Position 5 Casing Flanges	2	150# RF ANSI	■	■	■	■
	3	300# RF ANSI	■	■	■	■
Position 6 O-Rings*	T	Teflon	■	■	■	■
Position 7 Containment Can	Z	Zirconia (Ceramic)	■	■	■	■
Position 8 Magnetic Coupling	L	NdFeB 1.5"	■	■	■	⊗
	M	NdFeB 2.0"	■	■	■	⊗
	Q	SmCo 1.5"	■	■	■	⊗
	R	SmCo 2.0"	■	■	■	⊗
	5	NdFeB 2.0"	⊗	⊗	⊗	■
	6	NdFeB 3.0"	⊗	⊗	⊗	■
	7	SmCo 2.0"	⊗	⊗	⊗	■
	8	SmCo 3.0"	⊗	⊗	⊗	■
Position 9 Mounting	0	Close-Coupled	■	■	■	■
	1	Power Frame	■	■	■	■
Position 10 Motor Frame Size (Select if Pos. 9 = 0)	A	56C/56HC	■	■	■	⊗
	B	143/145TC	■	■	■	⊗
	C	182/184TC	■	■	■	■
	D	213/215TC	■	■	■	■
	E	254/256TC	■	■	■	■
	F	284/286TC or TSC	⊗	⊗	⊗	■
	G	324/326TC or TSC	⊗	⊗	⊗	■
Position 11 Barrier Seal Face Material	1	Silicon Carbide	■	■	■	■
Position 12 Barrier Seal O-Rings	V	Viton	■	■	■	■
	K	Kalrez	■	■	■	■

* For Casing & Containment Can

■ = Available

⊗ = Not Available

CF = Consult Factory