

SERIES	MODEL	CONFIGURATION	SEAL TYPE
Max-Series	M0, M1, M2, M3	Sealed Gear Pump Close-Coupled with NPT or BSPT Ports.	Single Mechanical Seal or Double Mechanical Seal

UNITS: inches [mm]

MOTOR	"A"	"B"	"C"	"D"	"E"	"F"	"G"	"H"
56C	9.02 [229.0]	7.32 [186.0]	5.75 [146.1]	4.00 [101.6]	3.50 [88.9]	9.89 [251.1]	3.00 [76.2]	4.88 [123.8]
143/145TC	9.02 [229.0]	7.32 [186.0]	5.75 [146.1]	4.00 [101.6]	3.50 [88.9]	10.20 [259.0]	4.00 [101.6]	5.50 [139.7]
IEC 71 B5	9.02 [229.0]	7.32 [186.0]	5.05 [128.1]	3.30 [83.7]	2.80 [71.0]	9.09 [231.0]	3.54 [90.0]	4.41 [112.0]
IEC 80 B5	9.02 [229.0]	7.32 [186.0]	5.40 [137.1]	3.65 [92.7]	3.15 [80.0]	9.29 [236.0]	3.94 [100.0]	4.92 [125.0]
IEC 90 B5	9.02 [229.0]	7.32 [186.0]	5.79 [147.1]	4.04 [102.7]	3.54 [90.0]	9.53 [242.0]	3.94 [100.0]	5.51 [140.0]

